

Features

- **StiffBACK™ DOUBLE HULL** design increases stiffness, safety and durability.
- **QuickFIT™** Railing easily connects to any number of boats to form any size and shape floating platform for any mission. Connection takes about 20 seconds and can be released in 2 seconds.
- Complies with all current USCG regulations including upright and level flotation. It will not sink with recommended max load when completely flooded.
- Removable **SEATool™** Boxes provide seating and equipment storage. Need a flat floor? Pull 4 pins and throw the boxes overboard, they float.
- Modular seat spacing for "dragging" recovery operations. Each seat is 4 feet from the next, even the next seat in the next boat!
- Foam flotation is built in and prevents sinking when flooded.
- Standard equipment includes Navigation Lights, Bilge Pump, 2 **SEATool™** Boxes, 4 **FloatROPES™**
- Non-skid Flat Floor coated with high tech durable coating. A flat gray interior coating minimizes glare.

The All New...

RESCUEONE®

1673-X2™ Connector Boat®



844-471-2628 • WWW.RESCUEONEBOATS.US

A Division of Marine ONE Corporation

Technical Specifications

RescueONE® 1673-X2™ Connector Boat®

Technical Specifications US-Metric

(Note: Bid Specs are available upon request.)

1673-X2™ Connector Boat® (Hull only)

Length 16'6" - 5.0 m
 Beam 6'3" - 1.87 m Bottom Width 60" - 1.52 m
 Side Depth-Outside 21" - 53 cm
 Side Depth - Inside 19" - 48 cm
 Height With Motor 42" - 106 cm
 Height With Light Bar Mount (not folded) 62" - 157 cm
 Height With Light Bar Mount (folded) 30" - 76 cm
 Interior Operating Space = 64 Sq Ft - 6.0 sq m
 (with SEATool™ Boxes Removed)
 Dry Weight 580 Lbs.- 262 Kg
 Hull Material 0.100 thickness marine aluminum
 Double Hull with 2" foam separating them

For full speed operation including emergency maneuvers:

Max Recommended Weight Capacity 1800 Lbs - 816 Kg
 Max Persons Weight 1250 Lbs - 567 Kg
 Max Number of Persons - 8
 Max Recommended Horsepower:
 -With Tiller steer outboard - 50hp
 -With Remote Steer/ Console - 70hp

1673-SS Transport™ Trailer

Length 20'2" - 6.1 m
 (with SpaceSAVER™ tongue extended in towing position)
 Length 17'6" - 5.4 m
 (with SpaceSAVER™ tongue folded in storage position)
 Width 7'9" - 2.3 m

Height With Motor 5'5" - 1.6 m
 Height With Light Bar Not Folded 7'3" - 2.2 m
 Height With Light Bar Folded 4'7" - 1.4 m
 GVWR 2720 Lbs - 1234 Kg
 Max Weight Capacity 2000 Lbs - 907 Kg

TwinTransport™ Trailer

Length 22'5" - 6.83 m
 Width 7'9" - 2.3 m
 Height (Trailer Only) 8'4" - 2.5 m
 Height With Boat On Top Rack 9'7" - 2.9 m
 Electric Winch capacity 8500 Lbs - 3855 Kg
 GVWR 4250 Lbs - 1928 Kg
 Max Weight Capacity 2800 Lbs - 1270 Kg

BID SPECS AVAILABLE

Assistance with preparing custom bid specifications is available. Please contact us for details.



Boat Connector Posts



Removable SEATool™ Boxes